

Amendment and Response

Page 2 of 12

Timothy L. HOOPMAN et al.

Serial No.: 09/955,604

Confirm. No.: 1214

Filed: 19 September 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

In the Claims

Please amend claims 23, 24, 30-32, 56, 57, 63, 64, 92, 93, 113, 114, 136, 143, and 151-153. The amended claims are provided below in clean form. Per 37 C.F.R. § 1.121, amended claims are also shown in Appendix A with notations to indicate changes made (for convenience, all pending claims are provided in Appendix A).

23. (Amended) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, and the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second and third plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first and third plurality of angles, and wherein each of the cavities has a single opening.

24. (Amended) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape and fourth plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second, third, and fourth plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first, third, and fourth plurality of angles, wherein at least one of the angles of

Amendment and Response

Page 3 of 12

Timothy L. HOOPMAN et al.

Serial No.: 09/955,604

Confirm. No.: 1214

Filed: 19 September 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

B2
the third plurality is different from all of the angles of the first, second, and fourth plurality of angles, and wherein each of the cavities has a single opening.

30. (Amended) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first, a second, and a third group, wherein a first group of cavities has a first shape, a second group of cavities has a second shape, a third group of cavities has a third shape, wherein the first, second, and third shapes are all different, and wherein each of the cavities has a single opening.

B3
31. (Amended) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first, a second, and a third group, wherein a first group of cavities has a first size, a second group of cavities has a second size, a third group of cavities has a third size, wherein the first, second, and third sizes are all different, and wherein each of the cavities has a single opening.

32. (Amended) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defined by substantially distinct and discernible boundaries which include substantially specific dimensions, wherein a first cavity has specific first dimensions, a second cavity has specific second dimensions, and a third cavity has specific third dimensions, each of said cavities has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one cavity meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first cavity is different from all the angles of intersection of said second and third cavities, wherein at least one angle of intersection of said second cavity is different from all the angles of intersection of said first and third cavities, and wherein each of the cavities has a single opening.

Amendment and Response

Page 4 of 12

Timothy L. HOOPMAN et al.

Serial No.: 09/955,604

Confirm. No.: 1214

Filed: 19 September 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

56. (Amended) A method of making a production tool, the method comprising:

creating a design for a production tool for manufacturing an abrasive article, the production tool comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, and the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second and third plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first and third plurality of angles, and wherein each of the cavities has a single opening; and forming the production tool using the design.

B4 57. (Amended) A method of making a production tool, the method comprising:

creating a design for a production tool for manufacturing an abrasive article, the production tool comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape and fourth plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second, third, and fourth plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first, third, and fourth plurality of angles, wherein at least one of the angles of the third plurality is different from all of the angles of the first, second, and fourth plurality of angles, and wherein each of the cavities has a single opening; and forming the production tool using the design.

Amendment and Response

Page 5 of 12

Timothy L. HOOPMAN et al.

Serial No.: 09/955,604

Confirm. No.: 1214

Filed: 19 September 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

B5

63. (Amended) A method of making a production tool, the method comprising:
creating a design for a production tool for manufacturing an abrasive article, the production tool comprising a plurality of cavities defining at least a first, a second group, and a third group, wherein a first group of cavities has a first shape, a second group of cavities has a second shape, a third group of cavities has a third shape, wherein the first, second, and third shapes are all different, and wherein each of the cavities has a single opening; and
forming the production tool using the design.

64. (Amended) A method of making a production tool, the method comprising:
creating a design for a production tool for manufacturing an abrasive article, the production tool comprising a plurality of cavities defining at least a first, a second group, and a third group, wherein a first group of cavities has a first size, a second group of cavities has a second size, a third group of cavities has a third size, wherein the first, second, and third sizes are all different, and wherein each of the cavities has a single opening; and
forming the production tool using the design.

B6

92. (Amended) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, and the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second and third plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first and third plurality of base edge lengths, and wherein each of the cavities has a single opening.

Amendment and Response

Page 6 of 12

Timothy L. HOOPMAN et al.

Serial No.: 09/955,604

Confirm. No.: 1214

Filed: 19 September 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

B6

93. (Amended) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape including a base and fourth plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the third plurality is different from all of the base edge lengths of the first, second, and fourth plurality of base edge lengths, and wherein each of the cavities has a single opening.

B7

113. (Amended) A method of making a production tool, the method comprising:
creating a design for a production tool for manufacturing an abrasive article, the production tool comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, and the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second and third plurality of base edge lengths, wherein at least one of the base edge lengths of the second

Amendment and Response

Page 7 of 12

Timothy L. HOOPMAN et al.

Serial No.: 09/955,604

Confirm. No.: 1214

Filed: 19 September 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

plurality is different from all of the base edge lengths of the first and third plurality of base edge lengths, and wherein each of the cavities has a single opening; and
forming the production tool using the design.

114. (Amended) A method of making a production tool, the method comprising:

creating a design for a production tool for manufacturing an abrasive article, the production tool comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape including a base and fourth plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the third plurality is different from all of the base edge lengths of the first, second, and fourth plurality of base edge lengths, and wherein each of the cavities has a single opening; and

forming the production tool using the design.

136. (Amended) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third row of cavities, wherein the cavities each have a geometric shape including a base and a plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first row of cavities is different from all the base edge lengths of the second and third rows of cavities, wherein at least one of the base edge lengths of

Amendment and Response

Page 8 of 12

Timothy L. HOOPMAN et al.

Serial No.: 09/955,604

Confirm. No.: 1214

Filed: 19 September 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

B8
the second row of cavities is different from all the base edge lengths of the first and third row of cavities, and wherein each of the cavities has a single opening.

B9
143. (Amended) A production tool suitable for use in manufacturing an abrasive article comprising first, second, and third cavities, wherein the first cavity has a first geometric shape including a base and a first plurality of base edge lengths forming the base of the geometric shape, the second cavity has a second geometric shape including a base and a second plurality of base edge lengths forming the base of the geometric shape, and the third cavity has a third geometric shape including a base and a third plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality of base edge lengths is different from all the base edge lengths of the second and third plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality of base edge lengths is different from all the base edge lengths of the first and third plurality of base edge lengths, and wherein each of the cavities has a single opening.

B10
151. (Amended) A method of making a production tool, the method comprising:
creating a design for a production tool for manufacturing an abrasive article, the production tool comprising a plurality of cavities defined by substantially distinct and discernible boundaries which include substantially specific dimensions, wherein a first cavity has specific first dimensions, a second cavity has specific second dimensions, and a third cavity has specific third dimensions, each of said cavities has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one cavity meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first cavity is different from all the angles of intersection of said second and third cavities, wherein at least one angle of intersection of said second cavity is different from all the angles of intersection of said first and third cavities, and wherein each of the cavities has a single opening; and
forming the production tool using the design.

Amendment and Response

Page 9 of 12

Timothy L. HOOPMAN et al.

Serial No.: 09/955,604

Confirm. No.: 1214

Filed: 19 September 2001

For: **TOOLS TO MANUFACTURE ABRASIVE ARTICLES**

152. (Amended) A method of making a production tool, the method comprising:

creating a design for a production tool for manufacturing an abrasive article, the production tool comprising a first, second, and third row of cavities, wherein the cavities each have a geometric shape including a base and a plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first row of cavities is different from all the base edge lengths of the second and third rows of cavities, wherein at least one of the base edge lengths of the second row of cavities is different from all the base edge lengths of the first and third row of cavities, and wherein each of the cavities has a single opening; and

forming the production tool using the design.

153. (Amended) A method of making a production tool, the method comprising:

creating a design for a production tool for manufacturing an abrasive article, the production tool comprising first, second, and third cavities, wherein the first cavity has a first geometric shape including a base and a first plurality of base edge lengths forming the base of the geometric shape, the second cavity has a second geometric shape including a base and a second plurality of base edge lengths forming the base of the geometric shape, and the third cavity has a third geometric shape including a base and a third plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality of base edge lengths is different from all the base edge lengths of the second and third plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality of base edge lengths is different from all the base edge lengths of the first and third plurality of base edge lengths, and wherein each of the cavities has a single opening; and

forming the production tool using the design.